

Installation JavaSpaces (simBio_JavaSpaces servers and workers)

Table of contents

- 1 Hardware Preparation..... 2
- 2 Software Installation..... 2
 - 2.1 Install Java..... 2
 - 2.2 Install Jini..... 2
 - 2.3 Install simBio_JavaSpaces servers..... 2
 - 2.4 Install simBio_JavaSpaces workers..... 3

Preparing the Operational Environment for simBio_JavaSpaces servers and workers.

1. Hardware Preparation

Because simBio is written in Java, it can be executed on several operating systems and simBio_JavaSpaces servers and workers can be used on different types of computers. See [Hardware Preparation](#) for more information on hardware requirement.

2. Software Installation

Software installation on simBio_JavaSpaces servers and workers.

2.1. Install Java

Install Java on both simBio_JavaSpaces servers and workers by following the instruction [Java](#).

2.2. Install Jini

To set up the system (PC clusters) the next step is to install Jini on simBio_JavaSpaces servers.

Download and install Jini Starter Kit from [Jini](#). Follow the installation process for your operating systems.

Installation folder

If you use Windows it is recommended to install Jini at C:\lib\

2.3. Install simBio_JavaSpaces servers

The next step to set up the system (PC clusters) is to install the package simBio_server-*.bin.zip on simBio_JavaSpaces servers.

There are two ways to get the package. The first is to download the release package by following the instruction [Download](#), but to download the file simBio_server-*.bin.zip instead. The second way is to build the simBio_JavaSpaces distributed packages. This is done by right clicking on the file build.xml in the simBio_JavaSpaces project and select [Run As] -> [Ant Build]. After the build is finished, the distributed packages can be found in the folder target\dist\.

Installation folder

It is recommended to install the simBio_JavaSpaces servers in the same folder as Jini was installed.

Auto Startup

To start the simBio_JavaSpaces servers automatically when the computers are turned on, it is recommended to use the operating systems auto startup functionality for the DOS batch file startJavaSpaces.bat or the UNIX/LINUX Shell Script startJavaSpaces.sh depending on which operating systems the servers are running on.

2.4. Install simBio_JavaSpaces workers

The final step to set up the system (PC clusters) is to install the package simBio_worker-*.bin.zip on simBio_JavaSpaces workers.

There are two ways to get the package. The first is to download the release package by following the instruction [Download](#), but to download the file simBio_worker-*.bin.zip instead. The second way depends on if the RemoteClient will be used or not. If the RemoteClient will be used then after following the instruction, [Getting RemoteClient](#), build the distributed package by right clicking on the file build.xml in the RemoteClient project and select [Run As] -> [Ant Build]. After the build is finished, the distributed package can be found in the folder target\dist\. If the RemoteClient will not be used then can the instruction giving in [Install simBio JavaSpaces servers](#) be followed in order to build the simBio_JavaSpaces distributed packages.

Installation folder

If you use Windows it is recommended to install the simBio_JavaSpaces workers at C:\lib\simBio\

Auto Startup

If the RemoteClient will be used it is recommended to use the operating systems auto startup functionality for the DOS batch file commandServer.bat or the UNIX/LINUX Shell Script commandServer.sh depending on which operating systems the CommandServers are running on, to start the CommandServers automatically when the computers are turned on.

If the RemoteClient is **not** used it is recommended to use the operating systems auto startup functionality for the DOS batch file startWorker.bat or the UNIX/LINUX Shell Script startWorker.sh depending on which operating systems the workers are running on, to start the simBio_JavaSpaces workers automatically when the computers are turned on.